



Generation II Entree Bath

ARCHITECTURAL SPECIFICATIONS & ROUGH-IN INFORMATION

STANDARD LENGTH MODELS

Exterior Dimensions

Width	All models below (Door Closed)	36"
Width	All models below (Door Opened)	34.25"
Length	MB-59-AV —Alcove Placement	59.5"
Length	MB-68-AVH —Head End Corner Placement	62.5"
Length	MB-68-AVF —Foot End Corner Placement	62.5"
Length	MB-68-AV —Standard Wall Placement	65.5"
Height	All models above to the top of controls	46.5"

Optional Recessed Access Door Available for Island or Peninsula Placement

Interior Dimensions

Length-Straight	45"
Length-Diagonal	47"
Seat Depth	22" at Widest Point
Seat Area Width (w/ Door Closed)	25"
Seat Height	21.5"

Specifications

Back Flow Prevention:	Double check valves for shower wand complies with CSA B64.7, UPC, Certified to NSF/ANSI 372, ASSE 1035—"Laboratory Faucet Vacuum Breakers". Fill: 1.5" A gap above rim complies with National Plumbing Standards. (See plumbing standards below.) Note: The factory provided backflow prevention is the most widely accepted. Local codes may require changes. The local plumbing contractor is responsible for any changes.
BathAire^(SM) Outlets:	4 with 12 ports each for a total of 48 warm air massage outlets.
Door Seal:	Seal certified by Warnock Hersey to the ASME A112.19.15-2005, CSA B45.0-02 (R2008) and ANSI Z124.1.2 (2008) standards to ensure long lasting durability for bathtubs with pressure sealed doors. Highly resistant to oils, detergents and all water conditions.
Electrical:	Factory provided on board installed dead front Ground Fault Circuit Interrupter (GFCI): UL/CSA approved.
Installation Time:	1 hour (when water and electrical supplies meet the provided rough-ins.) Inspection and Adjustments: 1/2 hour
Motor Specs:	Door Motor: 115 V., 4.2 Amp, 1/3 H.P. BathAire ^(SM) Motor: 120 V, 11 Amp, 1.3 H.P. Variable speed with built-in 600 watt heating element for maximum comfort and control.
Room Size:	5' 11" wide x 9' 7 1/2" long minimum recommended. Can fit in smaller room--call MasterCare with dimensions.



Generation II Entree Bath

Plumbing Standards:	Warnock Hersey: CSA B45.5 (2008), ASME A112.19.15 (2005), CSA B45S1 (2004), ANSI Z124.1.2 (2005).
Switches:	Membrane and Pneumatic.
Thermometer: Tub	Solar / Digital temperature measurements.
Door/Entry:	Door full length of tub with tub seat extending over the floor surface.
Tub Fill/Shower:	Built-in thermostatic mixing valve certified to ASSE 1016-2005, ASME A112.18.1-2005, CSA B125 and UPC listed.
Tub Fill / Shower shut off:	Valves certified ASSE and UPC listed with ceramic disc controls.
Tub Shell:	Sanitary gel-coated FRP (Fiberglass Reinforced Polymer).
Tub Water Use:	45 gallons minimum with normal displacement 4 inches below overflow escutcheon.
Waste:	2" PVC schedule 40 pipe. DO NOT Hard-Plumb for ease of accessibility for servicing.
Water Connection:	¾" SS braided flex hose with female pipe thread connections.
Water Supply:	¾" hot and cold with shut-offs. Hot and cold water pressure 45-90 psi. Cold water to be 59° F. Hot water temperature should not exceed 120° F.
Weight Capacity:	500 lbs.
Fill Rate:	In excess of 17 GPM provided that the water lines are ¾", water pressure is at least 60 psi and the hot water is 120° F. Community and/or other environmental factors may affect the fill rate.

Establishment Registration 3003336913



- 1) ***Risk of electrical shock: Disconnect electric power source before installation and subsequent servicing.***
- 2) ***An equipment grounding terminal is provided in the field wiring compartment. To reduce the risk of electrical shock, this terminal must be connected to the grounding means provided in the electric supply panel with a conductor equivalent in size to the circuit conductors supplying this equipment.***
- 3) ***Install this unit in accordance with the U.S. National Electrical Code in the U.S.A. and the Canadian Electrical Code, Part I in Canada. Electrical service receptacle must be grounded for product with a 3 prong cord. In addition, the equipment ground bond wire must be attached per wiring diagram.***

IMPORTANT: This tub should be installed against a finished wall or alcove. DO NOT BUILD THE TUB IN so it can be moved for serviceability if necessary.



Generation II Entree Bath

EXTENDED LENGTH MODELS

Exterior Dimensions

Width	All models below (Door Closed).....	36"
Width	All models below (Door Opened).....	34.25"
Length	MB-59-AV (XL) —Alcove Placement	65.5"
Length	MB-68-AVH (XL) —Optional Head End Corner Placement.....	68.5"
Length	MB-68-AVF (XL) —Optional Foot End Corner Placement	68.5"
Length	MB-68-AV (XL) —Standard Wall Placement	71.5"
Height	All models above (top of controls.....)	46.5"

Optional Recessed Access Door Available For Island and Peninsula Placement.

Interior Dimensions

Length-Straight.....	51"
Length-Diagonal	52"
Seat Depth	22" at Widest Point
Seat Area Width (w/ Door Closed)	25"
Seat Height.....	21.5"

Specifications

- Back Flow Prevention:** Double check valves for shower wand complies with CSA B64.7, UPC, Certified to NSF/ANSI 372, ASSE 1035—"Laboratory Faucet Vacuum Breakers". Fill: 1.5" a gap above rim complies with National Plumbing Standards. (See plumbing standards below.) Note: The factory provided backflow prevention is the most widely accepted. Local codes may require changes. The local plumbing contractor is responsible for any changes.
- BathAire^(SM) Outlets:** 4 with 12 ports each for a total of 48 warm air massage outlets.
- Door Seal:** Seal certified by Warnock Hersey to the ASME A112.19.15-2005, CSA B45.0-02 (R2008) and ANSI Z124.1.2 (2008) standards to ensure long lasting durability for bathtubs with pressure sealed doors. Highly resistant to oils, detergents and all water conditions.
- Electrical:** Factory provided on board installed dead front Ground Fault Circuit Interrupter (GFCI): UL/CSA approved.
- Installation Time:** 1 hour (when water and electrical supplies meet the provided rough-ins).
Inspection and Adjustments: 1/2 hour
- Motor Specs:** Door Motor: 115 V, 4.2 Amp, 1/3 H.P.
BathAire^(SM) Motor: 120 V., 11 Amp, 1.3 H.P. Variable speed with built-in 600 watt heating element for maximum comfort and control.
- Room Size:** 6' 5" wide x 10' 1½" long minimum recommended. Can fit in smaller room--call MasterCare with dimensions.



Generation II Entree Bath

Plumbing Standards:	Warnock Hersey: CSA B45.5 (2008), ASME A112.19.15 (2005), CSA B45S1 (2004), ANSI Z124.1.2 (2005).
Switches:	Membrane and Pneumatic.
Thermometer: Tub	Solar / Digital temperature measurements.
Door/Entry:	Door full length of tub with tub seat extending over the floor surface.
Tub Fill/Shower:	Built-in thermostatic mixing valve certified to ASSE 1016-2005, ASME A112.18.1-2005, CSA B125 and UPC listed.
Tub Fill / Shower shut off:	Valves certified ASSE and UPC listed with ceramic disc controls.
Tub Shell:	Sanitary gel-coated FRP (Fiberglass Reinforced Polymer).
Tub Water Use:	55 gallons minimum with normal displacement 4 inches below overflow Drain Handle.
Waste:	2" PVC schedule 40 pipe. DO NOT Hard-Plumb for ease of accessibility for servicing.
Water Connection:	¾" SS braided flex hose with female pipe thread connections.
Water Supply:	¾" hot and cold with shut-offs. Hot and cold water pressure 45-90 psi. Cold water to be 59° F. Hot water temperature should not exceed than 120° F.
Weight:	Approximately 500 lbs
Fill Rate:	In excess of 17 GPM provided that the water lines are ¾", water pressure is at least 60 psi and the hot water is 120° F. Facility and/or other environmental factors may affect the fill rate.

Establishment Registration 3003336913



- 1) *Risk of electrical shock: Disconnect electric power source before installation and subsequent servicing.*
- 2) *An equipment grounding terminal is provided in the field wiring compartment. To reduce the risk of electrical shock, this terminal must be connected to the grounding means provided in the electric supply panel with a conductor equivalent in size to the circuit conductors supplying this equipment.*
- 3) *Install this unit in accordance with the U.S. National Electrical Code in the U.S.A. and the Canadian Electrical Code, Part I in Canada. Electrical service receptacle must be grounded for product with a 3 prong cord. In addition, the equipment ground bond wire must be attached per wiring diagram.*

IMPORTANT: This tub should be installed against a finished wall or alcove. DO NOT BUILD THE TUB IN so it can be moved for serviceability if necessary.
